



NOTES:

GENERAL: ALL TRENCHING AND EXCAVATION SHALL COMPLY WITH MANITOBA'S WORKPLACE HEALTH AND SAFETY REGULATIONS

1. GBC-I, GBC-II, GBC-M OR CULVERT GRAVEL. REFER TO MSD-400.5 (NOTES 2 AND 3) IF TWO MATERIALS WILL BE USED.
2. CR-M50 SHALL BE USED AS SUBBASE IF CR-M100 OR CR-M125 IS USED AS GRANULAR FILL
3. FOR BITUMINOUS PAVEMENT. MINIMUM 100

ALL DIMENSIONS ARE IN MILLIMETRES, UNLESS SPECIFIED OTHERWISE

SEAL

APPROVALS	REVISIONS				MANITOBA STANDARD DRAWING			
ORIGINAL SIGNED BY: <u>DUSTIN BOOY</u> EXECUTIVE DIRECTOR OF HIGHWAY ENGINEERING SERVICES	No.	DESCRIPTION	BY	DATE	DATE		FROST TAPER DETAIL FOR EXISTING CULVERT	
	▲				OCTOBER 2025			
	▲				SCALE	SHEET		
	▲				N.T.S.	1 OF 1		
				MSD - 400.4				
ORIGINAL SIGNED BY: <u>TARA LISKE</u> EXECUTIVE DIRECTOR OF REGIONAL OPERATIONS				MSD - 400.4				