

LINE NO.	QTY. REQ'D.	DESCRIPTION	SIZE	MATERIAL (G40.21-M-300W U/N)	REMARKS
1	1	5.0 m STRAIGHT STANDARD (#17936)			
2	1	OCTAGONAL SECTION SHAFT	170 A/F-140 A/F x 3.038		
3	1	BASE PLATE	25 x 300 x 300	G40.21-M-300W	
4	1	CAP PLATE	12 x 180 φ		
5					
6	1	ACCESS PANEL			SEE SHEET NO. S15
7					
8	4	ANCHOR BOLT ASSEMBLY	29 DIA. x 1850	G40.21-M-300W	SUPPLIED BY OWNER SEE ANCHOR BOLT DWGS.
9					
10					
11					
12					
13					
14					

- NOTES:**
- ALL MATERIALS, EXCEPT STAINLESS STEEL ITEMS, SHALL BE HOT DIP GALVANIZED IN ACCORDANCE WITH ASTM A123-09 (PLUS LATEST REVISIONS) WITH NET RETENTION OF 610 g/m²
 - PROVIDE 'RAISED' STOCK CODE NUMBER WITH WELDING ELECTRODE.
 - SHIP WITH HANDHOLE COVERS INSTALLED.
 - STRUCTURE INSTALLED ON SPLIT-BASE (BREAKAWAY BASE) WITH 4-29 DIA. OR: BY BOLTS ON 292 BCD.
 - GRIND ALL SHARP POINTS AND EDGES.

BILL OF MATERIALS

REVISIONS



DATE	BY	DESCRIPTION

TRAFFIC SIGNAL STRUCTURE
LIGHT SERIES
5.0m STRAIGHT STANDARD

RELEASED FOR CONSTRUCTION
BY: _____



REDUCED DRAWING
N.T.S.



Manitoba
Infrastructure and Transportation
Traffic Engineering

DESIGN	BY: _____	CDM	DATE
CHECKED	BY: _____	SSR	SCALE
CHECKED	BY: _____	JGW	AS SHOWN
CHECKED	BY: _____	SSR	COMPONENT No.
			E-018 X
			SHEET No. S2