


**NOTES:**

- RISER CABLE EXISTING POLE MUST HAVE DRIP LOOP
- 3 SECTION OR 4 SECTION HEAD CAN BE ATTACHED TO 5m POLE (BOTH HAVE TO BE 3000mm ABOVE BASE PLATE TO BOTTOM OF HEAD).
- PEDESTRIAN SIGNAL HEAD HAS TO BE 3000mm FROM BASE PLATE TO TOP OF HEAD.
- SUPPORT STRAPPING SHALL BE STEEL HEAVY DUTY "SIGNODE" TYPE Z.R. COATED/GALVANIZED 19mm WIDE/0.61mm THICK USING "SIGNODE", #703 COATED/GALVANIZED SEALS. (SUBSTITUTES MAY BE APPROVED BY THE ENGINEER)
- ALL LENSES ARE LED.
- TWO BACKBOARDS CUT + USED TO FORM ONE - 4 SECTION BACKBOARD POP RIVETED TOGETHER.
- INSULATED BUSHING REQUIRED WHERE RISER CABLE ENTERS POLE.

REVISIONS	DATE	DESCRIPTION	BY

**Manitoba**   
 Infrastructure and  
 Transportation  
 TRAFFIC ENGINEERING

5 METER STRAIGHT POLE  
 Type 8

ORIGINAL  
 APPROVED BY: LUCIEN GAGNON

SCALE:	N.T.S.
DATE:	MAY/06
PREP. BY:	H.A.E.
E-112a	