

PEDESTRIAN HEADS:

THE PEDESTRIAN SIGNAL HEADS SHALL BE ASSEMBLED, INSTALLED AND CONNECTED BY THE CONTRACTOR AS REQUIRED BY LOCATION DRAWINGS.

HARDWARE:

- 2 x 38mm POLE PLATES.
- 2 x 450mm SUPPORT ARMS.
- 2 x THREADED 90° ELBOWS.
- 2 x 38mm HEXAGON LOCKING NUTS.
- 1 x 38mm CORK WASHER
- 2 LED BIMODAL LENSES

SUPPORT STRAPPING:


SUPPORT STRAPPING SHALL BE STEEL HEAVY DUTY "SIGNODE" TYPE Z.R. COATED/GALVANIZED 19mm WIDE/0.61 mm THICK USING "SIGNODE", #703 COATED/GALVANIZED SEALS. (SUBSTITUTES MAY BE APPROVED BY THE ENGINEER)

PEDESTRIAN PUSH BUTTONS:

PEDESTRIAN PUSH/BUTTON SHALL BE ASSEMBLED, INSTALLED AND CONNECTED BY THE CONTRACTOR AS REQUIRED BY LOCATION DRAWINGS. A 25mm APERTURE SHALL BE FIELD DRILLED IN THE STANDARD TO ALLOW ACCESS, FOR PUSH BUTTON WIRING AND FITTED WITH AN INSULATED BUSHING.

SAFE-T-BASE ASSEMBLY SHALL BE ASSEMBLED AND INSTALLED BY THE CONTRACTOR AS REQUIRED BY THE LOCATION DRAWINGS.

REVISIONS	DATE	DESCRIPTION	BY

Manitoba 
 Infrastructure and
 Transportation
 TRAFFIC ENGINEERING

LIGHT SERIES 3 m STRAIGHT STANDARD
 Type 1

ORIGINAL
 APPROVED BY: LUCIEN GAGNON

SCALE: N.T.S.
 DATE: JUNE/06
 PREP. BY: H.A.E.
 E-112h