

Sustainable Development

Environmental Stewardship Division
Environmental Approvals Branch
123 Main Street, Suite 160, Winnipeg, Manitoba, Canada R3C 1A5
T 204 945-8321 F 204-945-5229
www.gov.mb.ca/conservation/eal

File: 18414

November 20, 2017

Ms. Kristine Shields Chief Administrative Officer **RM of De Salaberry** Box 40 St-Pierre-Jolys, MB R0A 1V0

Dear Ms. Shields:

Re: De Salaberry Waste Disposal Ground, Permit 49464

Enclosed please find the Permit for your waste disposal ground.

Please note that failure to comply with any condition of the Permit may result in prosecution pursuant to the Waste Management Facilities Regulation.

Pursuant to Section 27 of The Environment Act, this Permit may be appealed to the Minister of Sustainable Development by any person who is affected by the issuance of this Permit within 30 days of the date of issue.

In addition to the enclosed Permit requirements, please be informed that all other applicable federal, provincial and municipal regulations and by-laws must be complied with.

If you have any questions concerning the Permit or procedures, please call Diane Oertel in Lac du Bonnet at (204) 345-1486 or via electronic mail at diane.oertel@gov.mb.ca.

Yours sincerely.

Tracey Braun, M.Sc.

Tracey Bear

Director

Environmental Approvals Branch

c: D. Labossiere/D.Smiley, Environmental Compliance and Enforcement Branch

NOTE: Confirmation of Receipt of this Permit No. 49464 (by the Permitee only) is required by the Director of Environmental Approvals. Please acknowledge receipt by signing in the space provided below and faxing a copy (letter only) to the Department by December 8, 2017.

On behalf of RM of De Salaberry Date



Waste Disposal Ground Operating Permit

Permit No: 49464 Client File: 18414

In accordance with the Waste Management Facilities Regulation, made under The Environment Act, the Rural Municipality of De Salaberry is hereby permitted to operate a Waste Disposal Ground, to be known as the RM of De Salaberry Waste Disposal Ground situated at NE 14-05-04 EPM in the Province of Manitoba.

THIS OPERATING PERMIT is subject to being AMENDED, SUSPENDED or REVOKED under section 7 of the Waste Management Facilities Regulation.

THIS OPERATING PERMIT is issued subject to the following TERMS AND CONDITIONS:

General Terms and Operating Conditions

- 1. This permit expires on October 31, 2022.
- 2. The Operator shall obtain approval in writing from the Director for any proposed alterations to the Facility before proceeding with the alteration.
- 3. The Operator shall maintain and operate the RM of De Salaberry Waste Disposal Ground (the Facility) in accordance with the most current version of the Waste Management Facilities Regulation (M.R. 37/2016) and this Operating Permit.
- 4. The Operator shall develop and maintain an Operations Manual detailing the operation and maintenance for this Facility in accordance with M.R. 37/2016, This manual should include but not be limited to a detailed list of waste and recyclable materials accepted, emergency and safety procedures, composting materials accepted and composting practices, location where materials not accepted are diverted to and active cell development, maintenance, cover and closure practices. The Operator shall provide the Manual to an Environment Officer upon request.
- 5. The Operator shall maintain a copy of the Manual developed pursuant to Condition 4 and a copy of this Operating Permit at the Facility or where the Facility is managed.

Materials Acceptance and Handling

- Materials collected for recycling or reuse must be segregated and temporarily stockpiled in clearly signed designated areas. These areas must be maintained to control weeds, vectors and quality of the materials. The Operator shall have the materials removed upon the request of an Environment Officer, within the timeframe specified.
- 7. The Operator shall remove any litter accumulated along the access road and around the perimeter of the site at minimum twice annually or as required by an Environment Officer.

Hazardous Wastes

8. The Operator shall collect, store and dispose of hazardous waste in accordance with The Dangerous Goods Handling and Transportation Act, and other Provincial and Federal Regulations.

Placement and Cover

- An Environment Officer must approve receipt of more than ten tonnes of dead animals from a single source and event. Dead animal material received at the Facility which may be identified as Specified Risk Material (SRM) must be handled in accordance with Canadian Food Inspection Agency requirements.
- 10. The Operator may use material other than soil for cover of the active area upon receiving written approval from the Director or Environment Officer.

Site Construction and Upgrading

- 11. The Operator shall have all waste disposal cells, modifications or alterations designed by and construction overseen by a Professional Engineer.
- 12. The Operator shall, prior to initiating any construction at the Facility, submit two paper copies and one electronic copy of final engineering design plans, sealed by an engineer(s), to the Director. The plans will show the engineering details of each new or altered component and the location of each new or altered component with respect to other components.
- 13. The Operator shall construct the Facility in accordance with the design plans submitted to the Director pursuant to Condition 12 of this Permit and subject to any terms and conditions set by the Director.
- 14. Notwithstanding Condition 12, construction shall be subject to the following conditions:
 - a) the Operator must provide for testing of all clay liners and cut-off walls by a qualified consultant to confirm compaction is 95% Standard Proctor Density on maximum lifts of 150 mm; and
 - b) all active areas or leachate containment developed from or with clay must be constructed to achieve a hydraulic conductivity of not more than 1x10⁻⁷ cm/s with a minimum thickness of 1 metre perpendicular to the surface. If appropriate or sufficient clay is not available an alternative proposal must be submitted to the Director for written approval prior to construction.
- 15. The Operator shall arrange with the designated Environment Officer a mutually acceptable time and date for any required soil sampling between the 15th day of October of any year, unless otherwise approved by the Environment Officer.
- 16. The Operator shall take and test undisturbed soil samples from the following:
 - a) the clay of new waste disposal cell(s);
 - b) leachate ponds; and
 - any clay component of the Facility requiring testing by the Director.
- 17. The number and location of samples and test methods will be specified by the designated Environment Officer up to a maximum of twenty (20) samples per cell or clay component of the Facility.

- 18. The Operator shall, prior to operation of any area tested in accordance with Condition 16, receive the approval of the Environment Officer for the results of the tests carried out pursuant to Condition 16 of this Permit.
- 19. The Operator shall, within 120 days of the completion of construction of a new waste disposal cell submit "record drawings" along with a construction report to the Director. The construction report shall comprise, without being limited to the following, the engineer's inspection dates and notes, density measurements (for clay lined facility), updated site plan showing the new cell and monitoring well installation logs, locations and background water samples (if applicable).

Burning of Specified Waste

- 20. The Operator shall only burn separated and readily combustible materials such as boughs, leaves, loose straw, paper products, cardboard, non-salvageable untreated wood, and packing materials derived from wood, and only when there is an appropriate volume of this material. Plywood, composite board or other materials constructed with glues, finishes or preservatives must not be burned.
- 21. The Operator shall not burn any other products or materials; including but not limited to plastics, composites, rubber, manures, chemically treated fabrics, mattresses, finished furniture, or manmade synthetics.

Monitoring and Reporting Requirements

- 22. Groundwater monitoring well samples shall be collected, stored and analyzed using approved field and laboratory techniques for dissolved analysis. The analytical results shall be retained in a format acceptable to Manitoba Sustainable Development.
- 23. The Operator shall sample the groundwater monitoring for those parameters identified in Appendix A once per year, or at a frequency as approved by the Director.
- 24. The Operator shall submit an annual report, in a format acceptable to the Director, detailing the sampling methodology, field observations and results of groundwater and surface water sampling analyses, complete with previous results and trends. The report shall be submitted to the designated Environment Officer no later than December 31 annually.

Revocation

25. This permit replaces Permit No. 41984 which is hereby rescinded.

November 20, 2017

Tracey Braun, M.Sc.

Director

Environmental Approvals Branch

Appendix A Ground Water Chemistry Parameters

Chemical Parameters	Chemistry Parameters
Inorganics	
Alkalinity – Total	Magnesium – Dissolved
Ammonia – Total	Manganese – Dissolved
Arsenic - Total	Mercury – Dissolved
Barium - Dissolved	Nitrate - Reported as N
Boron - Dissolved	Nitrite - Reported as N
Cadmium - Dissolved	Total Kjeldahl Nitrogen - Reported as N
Calcium - Dissolved	Total Phosphorous
Calcium Carbonate	Potassium Dissolved
Chloride	Silicon - Dissolved
Chromium Dissolved	Sodium - Dissolved
Conductivity	Total Dissolved Solids (TDS)
Copper – Dissolved	Sulphate
Iron - Dissolved	Uranium Dissolved
Lead - Dissolved	Zinc - Dissolved
Volatile Organic Compounds (VOC's)	
BTEX	
Other Organics	
Biological Oxygen Demand (BOD)	Chemical Oxygen Demand (COD)
Dissolved Organic Carbon (DOC)	
Field Parameters	
рН	Groundwater Elevation
Conductivity	Dissolved Oxygen
Temperature	

Note:

This Appendix is subject to revision at any time by the Director.
All metals (except Arsenic) are to be sampled for dissolved analysis.
Dissolved samples should be filtered in the field and preserved in the field at time of sampling. If dissolved samples are not to be filtered and preserved in the field then the Director and the Laboratory must be notified prior to sampling.